

Properties:

$$\tau = \mu \frac{du}{dy}$$

$$P = \rho R_{\text{gas}} T$$

$$\vec{F}_{\text{weight}} = \int \rho \vec{g} dV$$

$$SG = \rho / \rho_{\text{H}_2\text{O}}$$

$$P_{\text{gage}} = P_{\text{abs}} - P_{\text{atm}}$$

$$P_{\text{atm}} = 101.3 \text{ kPa}$$

$$\vec{F}_{\text{pressure}} = - \int p d\vec{A}$$

Hydrostatic Pressure: $p_{\text{lower}} = p_{\text{upper}} + \rho gh$ or $-\nabla p + \rho(\mathbf{g} - \mathbf{a}) = 0$

$$\bar{x} = \frac{\int xp(x)dA}{\int p(x)dA}$$

or $\bar{x}F_p = \int xp(x)dA$

$$p = p_0 - \rho gz + \frac{1}{2} \rho r^2 \Omega^2$$

Buoyancy: $F_{\text{buoyant}} = +\rho_w g V_{\text{sub}}$ $W = +\rho_o g V_{\text{obj}}$ $\rho_o / \rho_f = V_{\text{sub}} / V_{\text{obj}}$

Streamlines: $dy/dx = v/u$ $\psi = - \int v dx + f_1(y) = + \int u dy + f_2(x)$