

SAFETY DATA SHEET

Creation Date 16-Jan-2015 Revision Date 25-Apr-2019 Revision Number 4

1. Identification

Product Name Ethylenediamine

Cat No.: E479-4; E479-500; S80006

Synonyms 1,2-Diaminoethane; 1,2-Ethanediamine; Dimethylenediamine

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 3 Acute oral toxicity Category 4 Acute dermal toxicity Category 4 Skin Corrosion/irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Respiratory Sensitization Category 1 Skin Sensitization Category 1 Specific target organ toxicity (single exposure) Category 3 Target Organs - Respiratory system.

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor Harmful if swallowed Harmful in contact with skin

Causes severe skin burns and eye damage
May cause respiratory irritation
May cause an allergic skin reaction
May cause allergy or asthma symptoms or breathing difficulties if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion**

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS-No	Weight %	
Ethylene diamine	107-15-3	> 98	

Ethylenediamine

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing before re-use. Call a physician immediately.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Call a physician immediately.

Ingestion Do not induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. Breathing difficulties. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness,

lightheadedness, chest pain, muscle pain or flushing

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media No information available

Flash Point 34 °C / 93.2 °F

Method - No information available

Autoignition Temperature 385 °C / 725 °F

Explosion Limits

 Upper
 14.2 vol %

 Lower
 2.6 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx) Ammonia Hydrogen cyanide (hydrocyanic acid)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional ecological

information. Do not flush into surface water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe vapors or spray mist. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area. Corrosives area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethylene diamine	TWA: 10 ppm	(Vacated) TWA: 10 ppm	IDLH: 1000 ppm	TWA: 10 ppm
•	Skin	(Vacated) TWA: 25 mg/m ³	TWA: 10 ppm	TWA: 25 mg/m ³
		TWA: 10 ppm	TWA: 25 mg/m ³	STEL: 3 mg/m ³
		TWA: 25 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Ensure that eyewash stations and safety showers

are close to the workstation location. Ensure adequate ventilation, especially in confined

areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Long sleeved clothing. Skin and body protection

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Liquid **Physical State**

Ethylenediamine

Appearance Clear, Viscous Odor Ammonia-like

Odor Threshold No information available

11.9 (25 %) 8.5 °C / 47.3 °F Melting Point/Range

118 °C / 244.4 °F @ 760 mmHg **Boiling Point/Range**

34 °C / 93.2 °F **Flash Point Evaporation Rate** 0.91 (Butyl Acetate = 1.0)

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper 14.2 vol % Lower 2.6 vol % **Vapor Pressure** 12 mmHg @ 25 °C **Vapor Density** 2.07 (Air = 1.0)

Specific Gravity .8980 Soluble in water

Solubility Partition coefficient; n-octanol/water **Autoignition Temperature**

385 °C / 725 °F No information available **Decomposition Temperature** No information available

Viscosity

Molecular Formula C2H8N2 60.1 **Molecular Weight VOC Content(%)** 98

10. Stability and reactivity

No data available

Reactive Hazard None known, based on information available

Stable under normal conditions. Stability

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Acids, Acid anhydrides, Acid chlorides, Oxidizing agents **Incompatible Materials**

Hazardous Decomposition Products Nitrogen oxides (NOx), Ammonia, Hydrogen cyanide (hydrocyanic acid)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Component	LD30 Oral	LD30 Defilial	LOSO IIIII alatioii
Ethylene diamine	637 mg/kg (Rat)	LD50 = 560 mg/kg (Rabbit)	14.7 mg/L/4h (Rat)
	866 mg/kg (Rat)		

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Causes burns by all exposure routes Irritation

No information available Sensitization

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

ſ	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico

Ethylenediamine

| Ethylene diamine | 107-15-3 | Not listed |
|------------------|----------|------------|------------|------------|------------|------------|

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

Respiratory system STOT - single exposure

STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is:.. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

. Will likely be mobile in the environment due to its water solubility. **Mobility**

Component	log Pow
Ethylene diamine	-1 221

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

Ethylenediamine

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

TDG

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group || |

IATA

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

15. Regulatory information

United States of America Inventory

Component	CAS-No	TSCA	TSCA Inventory notification -	TSCA - EPA Regulatory
			Active/Inactive	Flags
Ethylene diamine	107-15-3	X	ACTIVE	-

Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Ethylene diamine	107-15-3	X	-	203-468-6	Х	X	Х	Χ	KE-13141

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	Component CWA - Hazardous CWA - Reportable Substances Quantities		CWA - Toxic Pollutants	CWA - Priority Pollutants
Ethylene diamine	X	5000 lb	-	-

Clean Air Act Not applicable

OSHA - Occupational Safety and

Not applicable

Health Administration

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs		
Ethylene diamine	5000 lb	5000 lb		

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know

Regulations

Component	omponent Massachusetts		Pennsylvania	Illinois	Rhode Island
Ethylene diamine	Х	X	Χ	<u> </u>	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard	
Ethylene diamine	Release STQs - 20000lb	

Other International Regulations

Mexico - Grade Serious risk, Grade 3

1	6	Othe	or ir	forr	nati	on
		()	-) II	11 ()1 1	пап	()

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 16-Jan-2015

 Revision Date
 25-Apr-2019

 Print Date
 25-Apr-2019

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS