# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 5.9 Revision Date 09/28/2017 Print Date 01/13/2018

# **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Acetic acid	
	Product Number Brand Index-No.	:	320099 Sigma-Aldrich 607-002-00-6	
	CAS-No.	:	64-19-7	

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 6310 USA	)3
Telephone Fax	: +1 800-325-5832 : +1 800-325-5052	

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Skin corrosion (Category 1A), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s) H226 H314	Flammable liquid and vapour. Causes severe skin burns and eye damage.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ protective clothing/ eye protection/ face

	protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

proto otion

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Synonyms	:	Glacial acetic acid
Formula	:	C <sub>2</sub> H <sub>4</sub> O <sub>2</sub>
Molecular weight	:	60.05 g/mol
CAS-No.	:	64-19-7
EC-No.	:	200-580-7
Index-No.	:	607-002-00-6
Registration number	:	01-2119475328-30-XXXX

#### Hazardous components

Component	oonent Classification Concent	
Acetic acid		
	Flam. Liq. 3; Met. Corr. 1; Skin	90 - 100 %
	Corr. 1A; Eye Dam. 1; H226,	
	H290, H314	

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

# 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CÁS-No.	Value	Control parameters	Basis
Acetic acid	64-19-7	TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Pulmonary function Upper Respiratory Tract irritation Eye irritation		on

STEL	15.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Pulmonary function		
Upper Respiratory Tract irritation Eye irritation		
ST	15.000000 ppm 37.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
Can be foun		s of 5-8% in vinegar
TWA	10.000000 ppm 25.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
Can be foun		s of 5-8% in vinegar
TWA	10.000000 ppm 25.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value in	mg/m3 is approxir	
TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
Pulmonary function Upper Respiratory Tract irritation Eye irritation		on
STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
Pulmonary f Upper Resp Eye irritation	iratory Tract irritation	on
TŴA	10 ppm 25 mg/m3	USA. NIOSH Recommended Exposure Limits
Can be foun	d in concentrations	s of 5-8% in vinegar
ST	15 ppm	USA. NIOSH Recommended
	37 mg/m3	Exposure Limits
		s of 5-8% in vinegar
TWA	10 ppm 25 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	mg/m3 is approxir	
PEL	10 ppm 25 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
STEL	15 ppm 37 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
C	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

# **Derived No Effect Level (DNEL)**

Derived no Litect Lever (Diall)				
Application Area Exposure routes		Health effect	Value	
Workers	Inhalation	Acute local effects	25 mg/m3	
Workers	Inhalation	Long-term local effects	25 mg/m3	
Workers	Skin contact	Long-term local effects	10mg/kg BW/d	
Consumers	Inhalation	Acute local effects	25 mg/m3	
Consumers	Inhalation	Long-term local effects	25 mg/m3	

# **Predicted No Effect Concentration (PNEC)**

Compartment	Value	
Soil	0.478 mg/kg	

Marine water	0.3058 mg/l
Fresh water	3.058 mg/l
Marine sediment	1.136 mg/kg
Fresh water sediment	11.36 mg/kg
Sewage treatment plant	85 mg/l
Aquatic intermittent release	30.58 mg/l

# 8.2 Exposure controls

# Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

# Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nature latex/chloroprene Minimum layer thickness: 0.6 mm Break through time: 32 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

# **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	pungent
c)	Odour Threshold	No data available
d)	рН	2.4 at 60.05 g/l

e)	Melting point/freezing point	Melting point/range: 16.2 °C (61.2 °F) - lit.	
f)	Initial boiling point and boiling range	117 - 118 °C (243 - 244 °F) - lit.	
g)	Flash point	40.0 °C (104.0 °F) - closed cup	
h)	Evaporation rate	No data available	
i)	Flammability (solid, gas)	No data available	
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 19.9 %(V) Lower explosion limit: 4 %(V)	
k)	Vapour pressure	73.3 hPa (55.0 mmHg) at 50.0 °C (122.0 °F) 15.2 hPa (11.4 mmHg) at 20.0 °C (68.0 °F)	
I)	Vapour density	No data available	
m)	Relative density	1.049 g/cm3 at 25 °C (77 °F)	
n)	Water solubility	completely miscible	
o)	Partition coefficient: n- octanol/water	log Pow: -0.17	
p)	Auto-ignition temperature	485.0 °C (905.0 °F)	
q)	Decomposition temperature	No data available	
r)	Viscosity	No data available	
s)	Explosive properties	No data available	
t)	Oxidizing properties	No data available	
Other safety information			
	Surface tension	28.8 mN/m at 10.0 °C (50.0 °F)	

# **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available

#### **10.4 Conditions to avoid** Heat, flames and sparks.

# 10.5 Incompatible materials

Oxidizing agents, Soluble carbonates and phosphates, Hydroxides, Metals, Peroxides, permanganates, e.g. potassium permanganate, Amines, Alcohols, Nitric acid

# 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

#### LC50 Inhalation - Mouse - 1 h - 5620 ppm

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Conjunctive irritation. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other. Blood:Other changes.

LC50 Inhalation - Rat - 4 h - 11.4 mg/l

LD50 Dermal - Rabbit - 1,112 mg/kg

No data available

#### Skin corrosion/irritation Skin - Rabbit Result: Causes severe burns.

Serious eye damage/eye irritation Eves - Rabbit

Result: Corrosive to eyes

#### **Respiratory or skin sensitisation** No data available

# Germ cell mutagenicity

No data available

# Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

# **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure No data available

#### Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

# Additional Information

RTECS: AF1225000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

# **12. ECOLOGICAL INFORMATION**

# 12.1 Toxicity

Toxicity to fish

(OECD Test Guideline 203)

Toxicity to daphnia and	EC50 - Daphnia magna (Water flea) - > 300.82 mg/l - 48 h
other aquatic	(OECD Test Guideline 202)
invertebrates	

#### 12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 30 d Result: 99 % - Readily biodegradable. Remarks: Expected to be biodegradable
Biochemical Oxygen	880 mg/g

Demand (BOD)

#### **12.3 Bioaccumulative potential** No data available

12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

Additional ecological No data available information

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

# DOT (US)

UN number: 2789 Class: 8 (3) Proper shipping name: Acetic acid, glacial Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No Packing group: II

IMDG

UN number: 2789 Class: 8 (3) Packing group: II Proper shipping name: ACETIC ACID, GLACIAL

EMS-No: F-E, S-C

# ΙΑΤΑ

UN number: 2789 Class: 8 (3) Proper shipping name: Acetic acid, glacial Packing group: II

# **15. REGULATORY INFORMATION**

# SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

# Massachusetts Right To Know Components

Massachusetts Right To Rhow Components		
	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
Met. Corr.	Corrosive to metals

#### **HMIS** Rating

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	2
Physical Hazard	0

# NFPA Rating

Health hazard:	3
Fire Hazard:	2
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

# **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.9

Revision Date: 09/28/2017

Print Date: 01/13/2018