

SAFETY DATA SHEET

Creation Date 11-Jun-2009	Revision Date 17-Jan-2018	Revision Number 4
	1. Identification	
Product Name	Toluene	
Cat No. :	T324-1; T324-4; T324-20; T324-200; T324-500; T T324FB-19; T324FB-50; T324FB-115; T324FB-20 T324POPB-200; T324RB-19; T324RB-115; T324 T324RS-28; T324RS-50; T324RS-115; T324RS-2 T324SK-4; T324SS-28; T324SS-50; T324SS-115	00; T324POP-200; RB-200; T324RS-19; 00; T324S-4;
CAS-No Synonyms	108-88-3 Tol; Methylbenzene	
Recommended Use Uses advised against	Laboratory chemicals. Not for food, drug, pesticide or biocidal product use	
Details of the supplier of the safe	ety data sheet	

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

Γ

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Category 2	
Category 2	
Category 2	
Category 2	
Category 3	
/stem (CNS).	
Category 2	
- ·	
Category 1	
`	Category 2 Category 2 Category 2 Category 3 ystem (CNS). Category 2

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Suspected of damaging the unborn child Causes damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC)

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. C	ompositio	on/Information on Ingred	lients
Component Toluene		CAS-No 108-88-3	Weight % >95
	4.	First-aid measures	
General Advice	If symptoms	persist, call a physician.	
Eye Contact	Rinse immed medical atter	iately with plenty of water, also under th tion.	ne eyelids, for at least 15 minutes. Get
Skin Contact	Wash off imn call a physici	nediately with plenty of water for at leas an.	t 15 minutes. If skin irritation persists,
Inhalation		n air. If not breathing, give artificial respi cur. Risk of serious damage to the lung	
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs naturally, have victim lean forward.		
Most important symptoms and effects	Breathing difficulties. Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting		
Notes to Physician	Treat symptomatically		
		re-fighting measures	
Suitable Extinguishing Media		ray, alcohol-resistant foam, dry chemic posed to fire with water spray.	al or carbon dioxide. Cool closed
Unsuitable Extinguishing Media	No information	on available	
Flash Point	4 °C / 39.2	°F	
Method -	No informatio	on available	
Autoignition Temperature	535 °C / 99	95 °F	
Explosion Limits Upper Lower Oxidizing Properties	7.1 vol % 1.1 vol % Not oxidising		
Sensitivity to Mechanical Impac Sensitivity to Static Discharge			

Specific Hazards Arising from the Chemical Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products Carbon monoxide (CO) Carbon dioxide (CO₂) Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health 3	Flammability 3	Instability 0	Physical hazards N/A	
	6. Accidental re	lease measures		
Personal Precautions			tilation. Remove all sources of	
Environmental Precautions		ignition. Take precautionary measures against static discharges. Should not be released into the environment. Do not flush into surface water or sanitary sewer system.		
Methods for Containment and Clea	ean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.			
	7. Handling	and storage		
Handling	ingestion and inhalation. E surfaces and sources of ig	nition. Use only non-sparking to all metal parts of the equipmer	ep away from open flames, hot pols. To avoid ignition of vapors by	
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area Keep away from heat and sources of ignition.		ilated place. Flammables area.	

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 50 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	TWA: 188 mg/m ³
		Ceiling: 300 ppm	TWA: 375 mg/m ³	
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm	_	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Long sleeved clothing.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physica	al and chemical properties
Physical State	Liquid
Appearance	Colorless
Odor	aromatic
Odor Threshold	1.74 ppm
рН	Not applicable
Melting Point/Range	-95 °C / -139 °F
Boiling Point/Range	111 °C / 231.8 °F @ 760 mmHg
Flash Point	4 °C / 39.2 °F
Evaporation Rate	2.4 (Butyl acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	7.1 vol %
Lower	1.1 vol %
Vapor Pressure	29 mbar @ 20 °C
Vapor Density	3.1
Specific Gravity	0.866
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	535 °C / 995 °F
Decomposition Temperature	No information available
Viscosity	0.6 mPa.s @ 20 °C
Molecular Formula	C7 H8
Molecular Weight	92.14

10. Stability and reactivity

Reactive Hazard	None known, based on information available	
Stability	Stable under normal conditions.	
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.	
Incompatible Materials	Strong oxidizing agents, Strong acids, Strong bases, Halogenated compounds	
Hazardous Decomposition Product	cts Carbon monoxide (CO), Carbon dioxide (CO ₂)	
Hazardous Polymerization	Hazardous polymerization does not occur.	
Hazardous Reactions	None under normal processing.	

11. Toxicological information

Acute Toxicity

Product Information

Component Information				
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat)1 h	
Toxicologically Synergistic Products Delayed and immediate effects	No information available as well as chronic effects fro	om short and long-term exposure	_	
Irritation	Irritating to eyes, respirat	ory system and skin		
Sensitization	No information available	No information available		
Carcinogenicity	The table below indicates	s whether each agency has listed ar	ny ingredient as a carcinogen.	

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects		Not mutagenic in A	MES Test			
Reproductive Effect	S	Experiments have shown reproductive toxicity effects on laboratory animals.				
Developmental Effe	cts	Developmental effects have occurred in experimental animals.				
Teratogenicity		Possible risk of harm to the unborn child.				
STOT - single expos STOT - repeated exp		Respiratory system Central nervous system (CNS) Kidney Liver spleen Blood				
Aspiration hazard		No information available				
Symptoms / effects delayed	,both acute and	d Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting				
Endocrine Disrupto	r Information	No information available				
Other Adverse Effect	ts	The toxicological properties have not been fully investigated.				

12. Ecological information

Ecotoxicity

Contains a substance which is:. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)
Persistence and Degradability Soluble in water Persistence is unlikely based on information available.				

Bioaccumulation/Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Toluene	2.7

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

1	Component	RCRA - U Series Wastes	RCRA - P Series Wastes
	Toluene - 108-88-3	U220	-

	14. Transport information
DOT UN-No Proper Shipping Name Hazard Class Packing Group TDG	UN1294 TOLUENE 3 II

UN-No Proper Shipping Name Hazard Class Packing Group	UN1294 TOLUENE 3 II
IATA	
UN-No	UN1294
Proper Shipping Name	TOLUENE
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1294
Proper Shipping Name	TOLUENE
Hazard Class	3
Packing Group	II
	15 Pequia

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Toluene	Х	Х	-	203-625-9	-		Х	Х	Х	Х	Х

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	Х

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Toluene	1000 lb 1 lb	-
California Proposition 65 This pro	oduct contains the following proposition 65 ch	emicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Toluene	108-88-3	Developmental	-	Developmental
U.S. State Right-to-Know	1			

Regulations						
Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island	
Toluene	X	X	X	Х	Х	

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

	16. Other information				
Prepared By	Regulatory Affairs Thermo Fisher Scientific				
	Email: EMSDS.RA@thermofisher.com				
Creation Date	11-Jun-2009				
Revision Date	17-Jan-2018				
Print Date	17-Jan-2018				
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).				

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS