

# SAFETY DATA SHEET

Creation Date 28-Apr-2009 Revision Date 17-Jan-2018 Revision Number 6

1. Identification

Product Name Acetone

Cat No.: A9-4; A9-20; A9-200; A11-1; A11-4; A11-20; A11-200; A11S-4; A13-20;

A13-200; A16F-1GAL; A16P-1GAL; A16P-4; A16S-4; A16S-20; A18-1; A18-4; A18-20; A18-20LC; A18-200; A18-200LC; A18-500; A18CU1300; A18C

A18FB-19; A18FB-50; A18FB-115; A18FB-200; A18P-4; A18POP-19;

A18POPB-50; A18RB-19; A18RB-50; A18RB-115; A18RB-200; A18RS-28; A18RS-50; A18RS-115; A18RS-200; A18S-4; A18SK-4; A18SS-19; A18SS-28; A18SS-50; A18SS-115; A18SS-200; A19-1; A19-4; A19RS-115; A19RS-200; A40-4; A928-4; A929-1; A929-4; A929-4LC; A929RS-19; A929RS-50; A929RS-200; A929SK-4;

A929SS-28; A929SS-50; A929SS-115; A929SS-200; A946-4; A946-4LC; A946FB-200; A946RB-19; A946RB-50; A946RB-115; A946RB-200; A949-1; A949-4; A949-4LC; A949CU-50; A949N-119; A949N-219; A949POP-19; A949RS-28; A949RS-50; A949RS-115; A949SK-1; A949SK-4; A949SS-19; A949SS-28; A949SS-50; A949SS-115;

A949SS-200; BP2403-1; BP2403-4; BP2403-20; BP2404-1; BP2404-4;

BP2404-SK1; BP2404-SK4; HC300-1GAL; S70091; 22050131;

22050295

**CAS-No** 67-64-1

**Synonyms** 2-Propanone; Dimethyl ketone; (Certified ACS, HPLC, OPTIMA, Histological,

Spectranalyzed, NF/FCC/EP, Pesticide, Electronic, GC Resolv, SAFE-COTE)

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** 

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2

Category 2

Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity (single exposure) Category 3
Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure)

Target Organs - Kidney, Liver, spleen, Blood.

### Label Elements

## **Signal Word**

Danger

### **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure



## **Precautionary Statements**

### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### Response

Get medical attention/advice if you feel unwell

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	>95

### 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point -20 °C / -4 °F

Method - Closed cup

Autoignition Temperature 465 °C / 869 °F

**Explosion Limits** 

Upper 12.8 vol %
Lower 2.5 vol %
Oxidizing Properties Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2) Formaldehyde Methanol

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>

HealthFlammabilityInstabilityPhysical hazards230N/A

Revision Date 17-Jan-2018 Acetone

### 6. Accidental release measures

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of **Personal Precautions** 

ignition. Take precautionary measures against static discharges.

Should not be released into the environment.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Up

# 7. Handling and storage

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Ensure Handling adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot

surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take

precautionary measures against static discharges.

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. **Storage** 

Keep away from heat and sources of ignition.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

**Environmental Precautions** 

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Acetone	TWA: 250 ppm	(Vacated) TWA: 750 ppm	IDLH: 2500 ppm	TWA: 1000 ppm
	STEL: 500 ppm	(Vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>
		(Vacated) STEL: 2400	TWA: 590 mg/m <sup>3</sup>	STEL: 1260 ppm
		mg/m³	_	STEL: 3000 mg/m <sup>3</sup>
		(Vacated) STEL: 1000 ppm		_
		TWA: 1000 ppm		
		TWA: 2400 mg/m <sup>3</sup>		

## Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations **Engineering Measures** 

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting/equipment.

**Personal Protective Equipment** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

FN166.

Skin and body protection Long sleeved clothing.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

**Physical State** Liauid **Appearance** Colorless

OdorsweetOdor Threshold19.8 ppm

pH 7

 Melting Point/Range
 -95 °C / -139 °F

 Boiling Point/Range
 56 °C / 132.8 °F

 Flash Point
 -20 °C / -4 °F

 Method Closed cup

**Evaporation Rate** 5.6 (Butyl Acetate = 1.0)

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 12.8 vol %

 Lower
 2.5 vol %

Vapor Pressure247 mbar @ 20 °CVapor Density2.0

Specific Gravity 2.0

O.790

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature465 °C / 869 °FDecomposition Temperature> 4°C

Viscosity 0.32 mPa.s @ 20 °C

Molecular FormulaC3 H6 OMolecular Weight58.08Refractive index1.358 - 1.359

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Heat, flames and sparks. Incompatible products. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated

compounds, Alkali metals, Amines

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Formaldehyde, Methanol

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
		> 7400 mg/kg (rat)	

**Toxicologically Synergistic**Products
Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane;
Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene;

Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 Irritating to eyes and skin

 Sensitization
 No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Revision Date 17-Jan-2018 Acetone

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed				

**Mutagenic Effects** No information available

No information available. **Reproductive Effects** 

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Central nervous system (CNS) Kidney Liver spleen Blood STOT - repeated exposure

No information available Aspiration hazard

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting:

May cause pulmonary edema: Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

The toxicological properties have not been fully investigated. Other Adverse Effects

# 12. Ecological information

**Ecotoxicity** 

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96	Oncorhynchus mykiss: LC50	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h
	h)	= 5540 mg/l 96h		EC50 = 12700  mg/L/48h
		Alburnus alburnus: LC50 =		EC50 = 12600  mg/L/48h
		11000 mg/l 96h		
		Leuciscus idus: LC50 =		
		11300 mg/L/48h		
		Salmo gairdneri: LC50 =		
		6100 mg/L/24h		

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

Will likely be mobile in the environment due to its volatility. **Mobility** 

Component	log Pow
Acetone	-0.24

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

# 14. Transport information

DOT

UN1090 **UN-No ACETONE Proper Shipping Name** 

**Hazard Class Packing Group** Ш

**TDG** 

UN-No UN1090 Proper Shipping Name UN1090 ACETONE

Hazard Class 3
Packing Group II

ATA

UN-No UN1090
Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

# 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

### International Inventories

	Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ī	Acetone	Х	Х	-	200-662-2	-		Х	Χ	Χ	Χ	Χ

#### Legend:

X - Listed

- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

## U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

## **U.S. Department of Homeland Security**

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Acetone	2000 lb STQ

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

Duran and Dur	Developer, Affaire
	16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 28-Apr-2009

 Revision Date
 17-Jan-2018

 Print Date
 17-Jan-2018

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**